



ITEM	DESCRIPTION / MATERIAL
VALVE BODY / END CAP	FORGED BRASS
STEM	NICKEL PLATED BRASS
BALL - (FULL PORT)	CHROME PLATED BRASS
SEATS	RTFE
THRUST WASHER	RTFE
STEM SEAL	VITON O-RINGS
HOUSING	POLYCARBONATE
FASTENERS	STAINLESS STEEL
BUSHINGS	BRASS
POWER CORD	18 AWGX3C - 8 FT. LONG
POWER	110 VAC 60 Hz PH 1
TEMPERATURE RANGE	35°F TO 165°F
MAX. WORKING PRESSURE	200 PSI
ADJUSTABLE CYCLE INTERVAL	5 MIN. TO 24 HRS.

MODEL	A	B	C	ENDS	BUSHINGS	DISCHARGE VOLUME / CYCLE
AD1B 1/2	5.0	3.75	4.72	1/2 - 14 NPT	1/4 X 1/2 NPT	.92 GAL. @ 80 PSI
AD1B 3/4	5.0	3.75	5.02	3/4 - 14 NPT	N/A	1.64 GAL. @ 80 PSI
AD1B 1	5.0	3.75	5.17	1 - 11.5 NPT	N/A	2.50 GAL. @ 80 PSI

**UNCONTROLLED DRAWING**

THIS PRINT IS THE PROPERTY OF DYNAPIP CONTROLS AND SHALL NOT BE COPIED, REPRODUCED, LOANED, OR DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SPECIFICALLY FURNISHED EXCEPT BY WRITTEN PERMISSION OF DYNAPIP CONTROLS.

<b>NO.</b> AD1B		<b>FILE NO.</b> SLB106	
<b>TITLE</b> DRAINMASTER			
<b>DR</b> MJP	<b>DATE</b> 10-19-05	<b>CH'KD</b> LJH	<b>DATE</b> 10-19-05
<b>ENGR</b> LJH	<b>DATE</b> 10-19-05		
			