

AVA Series Electric Actuators

The ultra-compact, ultra-versatile, ultra-value actuator



AVA Series SMART Electric Actuators

The SMART AVA comes with an OLED screen function displaying the actuator input/output status and any faults present. The screen features touch buttons to access the internal menu system allowing the user to change settings such as working angle, speed, and function.



AVA Series Standard Electric Actuators

The standard AVA is the perfect solution for applications requiring minimal features. It is available with basic on/off, failsafe or hi speed functionality. The standard AVA is constructed traditionally with preset internal cams striking micro-switches to stop the reversible motor in the required positions.

AVA Series Features

- Fully weatherproof to IP67
- Dome style local visual indicator
- Manual operation
- End of travel confirmation switches
- Female octagon drive output
- Multiple ISO 5211 mountings
- Anti-condensation heater
- Torque range from 177 in/lbs – 974 in/lbs

The DynaQuip Difference

For over eight decades DynaQuip has provided superior products and customer service. We offer flexible and innovative solutions for our unique customer needs. Our products are assembled, tested, and stored at our St. Clair, MO headquarters enabling us to offer quality assurance and industry best lead-times.

- **Industry-best lead times**
- **Personal customer service**
- **Superior quality products**
- **Flexible, innovative solutions**



AVA Series Electric Actuators





SMART AVA Options

- Hi Speed (1 sec, adjustable) *
- Modulating (10, 12, or 15 sec)
- Fail Close (10 or 15 sec)
- Fail Open (10 or 15 sec)

SMART AVA DIMENSIONS	A	B	C
SV17	3.83"	2.56"	3.31"
SV44	5.12"	4.33"	4.72"
SV70	7.44"	4.53"	4.36"
SV97	7.44"	4.53"	4.36"



Standard AVA DIMENSIONS	A	B	C
AV17	3.83"	2.56"	3.31"
AV44	5.12"	4.33"	4.72"
AV70	7.44"	4.53"	4.36"
AV97	7.44"	4.53"	4.36"



Standard AVA Options

- Hi Speed (1 sec; not adjustable) *
- On/Off (10, 12, or 15 sec)
- Fail Close (10 or 15 sec)



**Click to learn more
about the AVA Actuator**



Just Ask DynaQuip: 800-545-3636 | info@dynaquip.com | dynaquip.com

*Standard AVA Hi-Speed option is available in product #AV17XH

*Smart AVA Hi-Speed option is available in product #SV17UH

400046