



THREADED EXHAUST PORT
10-32 UNF

CATALOG NO.	DIMENSIONS							THREAD	PRESSURE RATING	WT. LBS.
	"A"	"B"	"C"	"D"	"E"	"F"	"H"			
VMH2-A9JP 1/4	.32	1.77	.89	1.80	3.70	.79 HEX	.64	1/4-18	200 PSI	.31
VMH2-A9JP 3/8	.38	1.77	.89	1.80	3.70	.79 HEX	.64	3/8-18	200 PSI	.29
VMH2-A9JP 1/2	.59	2.32	1.16	1.97	3.70	.98 OCT	.79	1/2-14	200 PSI	.47
VMH2-A9JP 3/4	.75	2.52	1.26	2.26	4.51	1.22 OCT	.91	3/4-14	200 PSI	.74
VMH2-A9JP 1	.95	3.19	1.59	2.42	4.51	1.58 OCT	1.06	1 - 1 1/2	200 PSI	1.19

11	HANDLE GRIP	VINYL, ORANGE w/ BLACK LETTERING
10	END CAP	BRASS, FORGED
9	BALL	BRASS w/ CHROME PLATE
8	BALL SEAT	REINFORCED PTFE, 15% GLASS
7	NUT	STEEL, DACROMET FINISH
6	HANDLE	STEEL, DACROMET FINISH
5	PACKING NUT	BRASS, NICKEL PLATED
4	STEM SEAL	PTFE
3	THRUST WASHER	REINFORCED PTFE, 25% CARBON
2	STEM	BRASS, NICKEL PLATED
1	BODY	BRASS, FORGED
ITEM	PART NAME	MATERIAL

UNCONTROLLED DRAWING

THIS PRINT IS THE PROPERTY OF DYNAQUIP CONTROLS AND SHALL NOT BE COPIED, REPRODUCED, LOANED, OR DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SPECIFICALLY FURNISHED EXCEPT BY WRITTEN PERMISSION OF DYNAQUIP CONTROLS.

NO. VMH2-A9JP FILE NO. SUB025

TITLE
BV EXHAUST
2 PC. BRASS
FPT F.P.

DR	DATE	CH'KD	DATE	ENGR	DATE
EJC	02-24-00	LJH	01-25-00	LJH	01-25-00

