



ITEM	DESCRIPTION / MATERIAL			
VALVE BODY / END CAP	FORGED BRASS			
STEM	NICKEL PLATED BRASS			
BALL - (FULL PORT)	CHROME PLATED BRASS			
SEATS	RTFE			
THRUST WASHER	RTFE			
STEM SEAL	VITON O-RINGS			
HOUSING	POLYCARBONATE			
FASTENERS	STAINLESS STEEL			
BUSHINGS	BRASS			
POWER SUPPLY	110 VAC TO 12 VDC			
TEMPERATURE RANGE	35°F TO 165°F			
MAX. WORKING PRESSURE	200 PSI			
ADJUSTABLE CYCLE INTERVAL	1 MIN. TO 14 DAYS			

MODEL	А	В	С	ENDS	BUSHINGS	DISCHARGE VOLUME/CYCLE	POWER CORD LENGTH
AD2A 1/2	5.0	3.75	4.72	1/2 - 14 NPT	1/4 X 1/2 NPT	3.1 GAL. @ 80 PSI	20'
AD2A 3/4	5.0	3.75	5.02	3/4 - 14 NPT	N/A	6.0 GAL. @ 80 PSI	20'
AD2A 1	5.0	3.75	5.17	1 - 11.5 NPT	N/A	7.7 GAL. @ 80 PSI	20'
AD2A 1- 1/4	5.0	3.75	5.44	1-1/4 - 11.5 NPT	N/A	12.8 GAL. @ 80 PSI	20'

UNCONTROLLED DRAWING

THIS PRINT IS THE PROPERTY
OF DYNAQUIP CONTROLS AND
SHALL NOT BE COPIED,
REPRODUCED, LOANED,
OR DISPOSED OF DIRECTLY
OR INDIRECTLY, NOR USED
FOR ANY PURPOSE OTHER THAN
THAT FOR WHICH IT IS
SPECIFICALLY FURNISHED
EXCEPT BY WRITTEN
PERMISSION OF
DYNAQUIP CONTROLS.

NO. AD2A

SUB 279

TITLE

DRAIN MASTER 12 VDC

MJP 04-10-18 MWS 07-06-15 MWS 07-06-15

