



**ALL VALVES ARE CERTIFIED TO
NSF/ANSI 372 FOR USE WITH POTABLE WATER**

MODEL	A	B	C	ENDS	BUSHINGS	DISCHARGE VOLUME/CYCLE	POWER CORD LENGTH
AD2A 1/2	5.0	3.75	4.72	1/2 - 14 NPT	1/4 X 1/2 NPT	3.1 GAL. @ 80 PSI	20'
AD2A 3/4	5.0	3.75	5.02	3/4 - 14 NPT	N/A	6.0 GAL. @ 80 PSI	20'
AD2A 1	5.0	3.75	5.17	1 - 11.5 NPT	N/A	7.7 GAL. @ 80 PSI	20'
AD2A 1-1/4	5.0	3.75	5.44	1-1/4 - 11.5 NPT	N/A	12.8 GAL. @ 80 PSI	20'

ITEM	DESCRIPTION / MATERIAL
VALVE BODY / END CAP	FORGED BRASS
STEM	NICKEL PLATED BRASS
BALL - (FULL PORT)	CHROME PLATED BRASS
SEATS	RTFE
THRUST WASHER	RTFE
STEM SEAL	VITON O-RINGS
HOUSING	POLYCARBONATE
FASTENERS	STAINLESS STEEL
BUSHINGS	BRASS
POWER SUPPLY	110 VAC TO 12 VDC
TEMPERATURE RANGE	35°F TO 165°F
MAX. WORKING PRESSURE	200 PSI
ADJUSTABLE CYCLE INTERVAL	1 MIN. TO 14 DAYS

UNCONTROLLED DRAWING

THIS PRINT IS THE PROPERTY OF DYNAQUIP CONTROLS AND SHALL NOT BE COPIED, REPRODUCED, LOANED, OR DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SPECIFICALLY FURNISHED EXCEPT BY WRITTEN PERMISSION OF DYNAQUIP CONTROLS.

NO.		AD2A			FILE NO.	SUB 279
TITLE						
DRAIN MASTER 12 VDC						
DR	DATE	CHKD	DATE	ENGR	DATE	
MJP	06-03-25	MWS	07-06-15	MWS	07-06-15	
						