



CATALOG NO.	DIMENSIONS						PRESSURE RATING	C _V	WT. LBS.
	A	B	C	D	E	F			
VME3-A90A 1½	.40	2.19	1.13	3.78	1.63	.53	2000 CWP 150 SWP	7	.5
VME3-A90A ¾	.54	2.62	1.31	3.78	1.73	.63	2000 CWP 150 SWP	12	.8
VME3-A90A 1	.68	3.12	1.60	5.10	2.08	.81	2000 CWP 150 SWP	25	1.4
VME3-A90A 1 ¼	.88	3.63	1.86	5.10	2.30	1.00	2000 CWP 150 SWP	38	2.4

11	SEAT RETAINER	STEEL C12L14, ZINC PHOS COAT
10	BALL	STAINLESS STEEL, TYPE 316
9	BALL SEAT	REINFORCED PTFE
8	HANDLE COVER	VINYL
8	HANDLE	STEEL, ZINC PLATE
7	NUT	STEEL, ZINC PLATE
6	SPRING WASHER	STEEL, ZINC PLATE
5	FOLLOWER	STAINLESS STEEL, 304
4	STEM SEAL	REINFORCED PTFE
3	THRUSTWASHER	REINFORCED PTFE
2	STEM	STAINLESS STEEL, TYPE 316
1	BODY	STEEL C12L14, ZINC PHOS COAT
ITEM	PART NAME	MATERIAL

UNCONTROLLED DRAWING

THIS PRINT IS THE PROPERTY
OF DYNAQUIP CONTROLS AND
SHALL NOT BE COPIED,
REPRODUCED, LOANED,
OR DISPOSED OF DIRECTLY
OR INDIRECTLY, NOR USED
FOR ANY PURPOSE OTHER THAN
THAT FOR WHICH IT IS
SPECIFICALLY FURNISHED
EXCEPT BY WRITTEN
PERMISSION OF
DYNAQUIP CONTROLS.

<i>NO.</i>	VME3-A90A	<i>FILE NO.</i> SUB017
------------	-----------	---------------------------

TITLE
BALL VALVE - VME SERIES
BAR STOCK - NPT THREADS

DR	DATE	CH' KD	DATE	ENGR	DATE
TAP	04-02-98	LJH	01-28-00	LJH	01-28-00

