



1/4 NPT  
INLET & EXHAUST  
PORTS

5/2 WAY 1/4 NPT  
SINGLE SOLENOID  
5 PORT - 2 POSITION  
NAMUR MOUNTING  
CE Certified

PRESSURE: 22 - 116 PSI  
TEMP: 23 - 140°F

CABLE CONNECTOR STANDARD	1/2" NPT CONDUIT CONNECTOR	
145855.06	145855.Y6	220 VAC 50/60 Hz
145855.04	145855.Y4	12 VDC
145855.03	145855.Y3	24 VDC
145855.02	145855.Y2	24 VAC 50/60 Hz
145855.01	145855.Y1	110 VAC 50/60 Hz
<b>PART NO.</b>	<b>PART NO.</b>	<b>VOLTAGE</b>

**UNCONTROLLED DRAWING**

THIS PRINT IS THE PROPERTY OF DYNAQUIP CONTROLS AND SHALL NOT BE COPIED, REPRODUCED, LOANED, OR DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SPECIFICALLY FURNISHED EXCEPT BY WRITTEN PERMISSION OF DYNAQUIP CONTROLS.

NO. 145855 SERIES FILE NO. SUB378

TITLE  
**SOLENOID VALVE**

DR	DATE	CH'KD	DATE	ENGR	DATE
MDC	05-23-25	MJP	05-02-16	MJP	05-02-16

