



Temp Range: 0° to 450°F

15	HANDLE NUT	BRASS
14	HANDLE COVER	PVC
13	HANDLE	304 SS
12	NUT	STEEL
11	BOLT	STEEL
10	END CAP	BRONZE B584 C84400
9	O-RING	VITON
8	SEAT	PTFE
7	BALL	A351 CF8M (316 SS)
6	GLAND	BRASS
5	O-RING	VITON
4	PACKING GLAND	PTFE
3	THRUST WASHER	PTFE
2	STEM	316 STAINLESS STEEL
1	BODY	BRONZE B584 C84400
ITEM NO.	DESCRIPTION	MATERIAL

MODEL NUMBER	DIMENSIONS								PRESSURE RATING	C _v	WT. (LBS)
	A	B	C	D	E	F	G	H			
VVA2.AMAP 1/4	0.44	2.68	1.59	2.60	4.33	1.65	1.97	.354	600	8	1.32
VVA2.AMAP 3/8	0.50	2.68	1.59	2.60	4.33	1.65	1.97	.354	600	10	1.32
VVA2.AMAP 1/2	0.59	2.68	1.59	2.60	4.33	1.65	1.97	.354	600	15	1.32
VVA2.AMAP 3/4	0.79	3.20	1.85	2.88	4.33	1.65	1.97	.354	600	35	2.03
VVA2.AMAP 1	0.98	3.46	2.10	3.31	4.92	1.65	1.97	.433	600	60	2.76
VVA2.AMAP 1 1/4	1.26	4.17	2.21	3.53	4.92	1.65	1.97	.433	600	105	3.42
VVA2.AMAP 1 1/2	1.50	4.72	2.88	4.25	5.91	1.97	2.76	.551	600	138	5.51
VVA2.AMAP 2	1.97	5.39	3.21	4.75	5.91	1.97	2.76	.551	600	270	8.38

UNCONTROLLED DRAWING

THIS PRINT IS THE PROPERTY OF DYNAQUIP CONTROLS AND SHALL NOT BE COPIED, REPRODUCED, LOANED, OR DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SPECIFICALLY FURNISHED EXCEPT BY WRITTEN PERMISSION OF DYNAQUIP CONTROLS.

NO. VVA SERIES FILE NO. SUB172

TITLE
BALL VALVE - VVA SERIES
3 PC - BRONZE - FEMALE NPT

DR	DATE	CH'KD	DATE	ENGR	DATE
MDC	08-09-24	LJH	08-26-05	LJH	08-26-05

